



# REPORT FLIGHT AND STRUCTURE TEST RESCUE

EN 12491 | 2001 | NfL II 91/09

**Manufacturer** VITAL PARACHUTE INC.  
**Address** 4th floor, Samjin bldg.  
 596 Cheonho-daero, Gwnagjin  
 Seoul 143-848 / Korea Republic

<b>Certification number:</b>	<b>EP 109.2014</b>
<b>Type/model:</b>	Octagon 55L (XXL)
<b>Total weight in flight:</b>	170 kg
<b>Serial number STRENGTH</b>	VPR-OTG141138
<b>Serial number FLIGHT</b>	VPR-OTG141038

## Measurement of Flight test rescue (5kg Tension)

Center Line   mm	7835 cm
Main Line 1   mm	7320 cm
Main Line 2   mm	
Number of cell:	24
Tolerance   mm	25 mm
Weight   grame	2665

TESTS	place:	date:	result:
<b>1. Deployment system strength test</b> A load of 700 N between each components	Villeneuve	26.11.2014	OK
<b>2. Speed of opening test - ref. A (2 times)</b> Time from the instant of free drop until a load of 200 N is sustained Opening time Opening time	Villeneuve	18.11.2014 21.11.2014	4.12 sec 4.89 sec
<b>3. Descent rate and stability test - ref. A and B (2 times)</b> The paraglider is released as the parachute begins to open, minimum 100 m descent. Stability 1 Sink rate 1 Stability 2 Sink rate 2	Villeneuve	18.11.2014 21.11.2014 18.11.2014 21.11.2014	Stable 4.9 m/sec Stable 5.1 m/sec
<b>4. Strength test 40 m/s opening shock (2 times)</b> The drop test device is accelerated to a straight line velocity of 40 m/s. Speed of opening is less than 5 seconds and shock not exceeded 15g Test 1 Test 2 Test 3	Illarsaz	20.11.2014 12.12.2014 12.12.2014	OK OK OK
<b>5. Interaction and stability test (piloted) - ref. C</b> a the emergency parachute is deployed from a paraglider in normal straight flight. b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.			not available not available not available
<b>6. Connecting strap</b> Minimum load capacity of 2400 daN			



# REPORT FLIGHT AND STRUCTURE TEST RESCUE

EN 12491 | 2001 | Nfl II 91/09

Manufacturer VITAL PARACHUTE INC.

Certification number:

**EP 109.2014**

Type/model:

Octagon 55L (XXL)

Serial number

VPR-OTG141038

Weather data, ref. 3 and B

Date / place	hPa	wind	tem	humidity
Villeneuve, November 18, 2014	960	0 km/h	9.6°	78.0%
	Corrected mass:	<b>164.14 kg</b>		
Villeneuve, November 21, 2014	969	0 km/h	8°	80.0%
	Corrected mass:	<b>166.62 kg</b>		

## Reference

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass ofr differences from ICAO standard atmosphere

$$m_{corr} := m_{dec} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Ground level atmospheric pressure at the test location: (p)

ICAO standard atmospheric pressure at MSL: (p<sub>0</sub>)

Ground level température at the test location: (T)

ICAO standard temperature at MSL: (T<sub>0</sub>)


Total weight in flight: (m<sub>dec</sub>)

Corrected mass: (m<sub>corr</sub>)


C. Only parachute with controls for steering and landing flare

GRAPHIQUE concerning Nfl II 91/09 "§ 6.1.8 inner container"

Max load attachement 1 = 263.9 kg



Max load attachement 2 = 182.4 kg







# REPORT FLIGHT AND STRUCTURE TEST RESCUE

EN 12491 | 2001 | Nfl II 91/09

Manufacturer VITAL PARACHUTE INC.

Certification number:


Type/model:

**EP 109.2014**

Octagon 55L (XXL)

GRAPHIQUE concerning Nfl II 91/09 "§ 6.1.4 connecting strap"

Max load = 2656,1 kg



## Air Turquoise SA

Route du Pré-au-Comte 8  
Case postale 10  
CH - 1844 Villeneuve  
Switzerland  
mobile: +41 79 202 52 30  
Tel. no : +41 21 965 65 65  
homepage: www.para-test.com

For Air Turquoise SA

EN & LTF Testing center  
Alain Zoller  
www.para-test.com

Villeneuve, 17.02.2015